

## Acry Glo<sup>®</sup> Accelerator CM0571082

### DESCRIPTION

CM0571082 Accelerator increases the speed of drying cure of Acry Glo<sup>®</sup> Acrylic Urethane Enamel coatings. Accelerator decreases the usable pot life of urethane enamels.

Use the minimum amount necessary to meet your drying schedules considering your in-shop conditions.

CM0571082 is the accelerator used for basecoat application, of the Acry Glo<sup>®</sup> Basecoat / Clearcoat Metallic System. See the Product Information Sheet for Acry Glo<sup>®</sup> Basecoat / Clearcoat Metallics.

Do not use in overall base topcoat painting of larger surfaces.

### COATING PROPERTIES

<b>Weight per Gallon:</b>	8.32
<b>Specific Gravity:</b>	1.00
<b>VOC:</b>	8.23 lb./gal (987 g/L)
<b>Workable Pot Life: (Limited)</b>	1 Hour 2-3 Hours Gelled

### MIXING INSTRUCTIONS

Maximum incorporation should be 1-ounce per admixed gallon or 1/4 ounce per admixed quart. This will usually speed up tape times on solid colors to approximately 2-3 hours @ 77°F / 25°C.

CM0571082 is most generally used for quick drying times on stripes, registration numbers, logos and panel repair painting.

Urethane accelerators are very reactive, and great care must be taken in the quantity used.

### EQUIPMENT CLEANUP

Use clean Ketone-type solvents. Do not allow material to cure inside equipment.

### SHELF LIFE

Shelf Life is applicable only for materials stored in unopened and undamaged original factory filled containers.

Minimum Storage Temp. 40°F / 4°C  
Maximum Storage Temp. 90°F / 32°C

CM0571082: 2 years

### USE OF SYSTEMS STATEMENT

Sherwin-Williams Aerospace Coatings have been developed and evaluated to be used as a "Total System". Our Aerospace primers have been developed to be compatible with the Jet Glo<sup>®</sup>/Acry Glo<sup>®</sup>/Accent<sup>™</sup> polyurethane paints. Use of products not manufactured by Sherwin-Williams Aerospace as replacement primer materials is not recommended. Paint failures, blistering, chemical resistance, inter-coat adhesion failure and paint gloss life issues may occur. For long-term integrity of the completed paint finish, use the complete Sherwin-Williams Aerospace finishing system.

### HEALTH AND SAFETY INFORMATION

Consult the Material Safety Data Sheets for product information regarding health, physical and environmental hazards, handling precautions and "First Responder" first-aid recommendations.

### PRODUCT INFORMATION

Please contact your Sherwin-Williams Aerospace Distributor or Representative for more information.

*NOTE: Product Information Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Information Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, The Sherwin-Williams Company cannot make any warranties as to the end result.*